



AGE

Stripping agent and graffiti remover

Availability			
Quantity per pallet	432	66	12
Packaging unit	12 x 0,75 l	5 l	25 l
Type of container	Tin bucket	Tin bucket	Tin bucket
Container code	01	05	25
Art. no.			
1368	■	■	■

Application rate

Approx. 0.3 - 0.5 l/m² per coat

Apply to a large enough trial area to determine the precise amount required.



Range of use

- Dissolving dispersion and pure acrylate varnishes, synthetic resin, nitro and spirit varnishes, matting, polishes and graffiti
- Wood surfaces, metallic and mineral substrates



Property profile

- Paste form
- Highly effective
- Long open working time
- Free from N-methyl pyrrolidone and chlorinated hydrocarbons, alkali-free
- Biodegradable

Characteristic data of the product

Density (20 °C)	1.04 kg/l
Viscosity	Approx. 7000 mPas
pH value (20 °C)	Approx. 8.5
Appearance	Yellowish

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates

- [Oberflächenschutz - BAST \(Bundesanstalt für Straßenwesen\)](#)

Additional information

- [Datenblatt über Inhaltsstoffe](#)

Possible system products

- [Funcosil FC \(0711\)](#)




- **Funcosil SNL (0602)**
- **Funcosil SN (0604)**
- **Graffiti Protection (0685)**

Preparation

- **Substrate preparation**
Mechanically remove coarse soiling.

Directions



- **Conditions for use**
Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C
- Apply the material using suitable equipment.
Action time depends on substrate, materials to be stripped, coating thicknesses and ambient climate.
After sufficient action time, remove the old coating mechanically using a suitable tool.
If needed, repeat the application.
Remove cleaning agent until no residues remain.

Tips on use

Make sure there is good ventilation.
Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.
Set up the necessary collection receptacles.
Extend the reaction time if necessary by covering with PE film.

Notes

The applicable regulations and legal requirements must be observed.
The relevant test certificates must be observed when planning and carrying out work.
Always set up a trial area/trial areas first.

Tools / Cleaning



Brush, surface brush (no artificial bristles), airless equipment

Clean tools with water immediately after use.

Remmers tools

- **Flächenstreicher (4540)**
- **Rollerbügel (4449)**
- **Heizkörperpinsel (4541)**

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Personal protective equipment

Respiratory protection with at least an A/P2 combination filter must be worn during spraying, together with safety goggles. Wear suitable protective gloves and clothing.

Disposal



Active ingredient residues and rinsing water that contains the active ingredients of the product must not be allowed to enter the surface water drainage system. Collect rinsing water and dispose of at a collection point or through the sewage system according to



local regulations. For more information, see advisory leaflet DWA-M 370 on “Waste and sewage from the cleaning of and coating removal from facades”.

The object must be reported to the relevant authorities.

Detergents Regulation
(EC) No 648/2004

5 - 15% aliphatic hydrocarbons;
< 5% soap, anionic surfactant

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.